

SILICON COATED FIBERGLASS SLEEVE

Fire sleeve is designed to protect hoses, wires and cables from the hazards of high heat and occasional flame. Fire sleeve is resistant to hydraulic fluids, oils, and fuels, protect employees from burns.

APPLICABLE STANDARD	DIN5510-2
CONSTRUCTION	Reinforcement: Fiberglass braid Cover: Silicone Rubber layer
TEMPERATURE RANGE:	Continuous: -54°C to +260°C



PART NO:	INNER DIA (MM)	THICKNESS (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG)
EFS-06	6	1.2	20	1.00
EFS-08	8	1.3	20	1.60
EFS-10	10	1.6	20	2.30
EFS-12	12	1.7	20	2.55
EFS-15	15	2.1	20	3.55
EFS-20	20	2.3	20	5.20
EFS-25	25	2.6	20	6.90
EFS-30	30	2.9	20	8.65
EFS-35	35	3.1	20	10.30
EFS-40	40	3.4	20	11.85
EFS-45	45	3.5	20	13.70
EFS-50	50	3.7	20	15.75
EFS-55	55	3.9	20	18.85
EFS-60	60	4.0	20	21.10
EFS-65	65	4.1	20	23.90
EFS-70	70	4.3	20	25.10
EFS-75	75	4.4	20	26.45
EFS-80	80	4.7	15	28.15
EFS-85	85	4.8	15	24.50
EFS-90	90	5.0	15	26.30
EFS-95	95	5.2	15	31.05
EFS-100	100	5.6	15	31.50