



# EC M200

## H.C. Material

- Made of Cr40 forge steel
- More than 6 months aging treatment
- 2mm thick harden layer

## Compact Design

- Pipeless hydraulic valve-block connection
- Stable pressure conduction
- Fits in repair workshop

## Battery Powered

- 12V or 24V battery powered
- Apply to mobile van or field service

## Strong-magnetic Dies

- Convenient for assembly and disassembly
- Crimping neatly and nice

Dies No.	Range	D	L
F32/03*	3.0-5.0	3	35
F32/06*	6.0-7.0	6	35
F32/08*	8.0-9.0	8	35
F32/10*	10.0-11.0	10	35
F32/12*	12.0-14.0	12	35
F32/15	15.0-17.0	15	45
F32/18	18.0-20.0	18	45
F32/20	20.0-22.0	20	45
F32/23	23.0-25.0	23	50
F32/26	26.0-28.0	26	65
F32/29	29.0-35.0	29	65
F32/36	36.0-45.0	36	80
F32/46	46.0-55.0	46	80
F32/51	51.0-61.0	51	80
F32/63	63.0-73.0	63	80
F32/70*	70.0-80.0	70	80

\* Available with special dies request.

EC M200 crimping machine is designed for field service when repairs must be made on-site, it is simple and compact in construction, easy to operate.

EC M200 is battery powered with 12V or 24V, provides 2000kN crimping force in a highly compact, ergonomic design. Portability and usefulness for service vehicles in various industries make them ideal for field service and emergency repairs.

H.C. Material	Forge Steel (Cr40)
Crimping Range	3-80mm (1/8"-3 1/6")
Max. Hydraulic Hose	2", 4SP (ID 51mm)
Max. Opening	+25mm (1")
Opening without Dies	118mm (4 5/8")
Accessible Diameter	118mm (4 5/8")
Master Die Length	80mm (3 1/6")
System Pressure	31.5Mpa
Max. Crimping Force	2000kN (200T)
Motor Power	3kW
Standard Voltage	12V/24V
Control	Automatic
Noise Level	60dB(A)
Weight	165kg
L x W x H	600*460*540mm

## Standard Accessories

- 10 sets of Standard Dies
- Pressure Gauge

## Optional Accessories

- Customized Dies
- Manual QC Tool
- Spare-parts Packet