

PP SPIRAL GUARD

TECHNICAL DATA SHEET

CONSTRUCTION: Polypropylene

APPLICATION:

The use of spiral hose guard is an economical and convenient method of protecting and extending the life of hydraulic and pneumatic hoses, cables, wires and rope from premature wear. Spiral guard will withstand the extremes of climate and operating conditions. Spiral guard wrap protects against abrasion, cuts, UV

TEMPERATURE RANGE: -50° J18 (-122°) to +80° (176°)



PART NO:	O.D	I.D	THICKNESS	STANDRAD LENGTH		APPLIED FOR HOSE O.D (MM)
	MM	MM	MM	M	FT	
PSG-12	12	9	1.5	61M	200FT	10-13
PSG-16	16	13	1.5	61M	200FT	14-17
PSG-20	20	16	2	61M	200FT	17-21
PSG-25	25	20.6	2.2	61M	200FT	22-27
PSG-32	32	27	2.5	61M	200FT	28-35
PSG-40	40	34.4	2.8	61M	200FT	36-45
PSG-50	50	43.6	3.2	30.5M	100FT	46-56
PSG-63	63	56	3.5	30.5M	100FT	57-67
PSG-75	75	66	4.5	22.5M	75FT	68-81
PSG-90	90	81	4.5	15M	50FT	82-100
PSG-110	110	100	5	15M	50FT	101-114
PSG-125	125	114	5.5	12M	40FT	115-127
PSG-140	140	127	6.5	12M	40FT	127-145